



RG70 • RG100 • RG100R



www.raycomfg.com

To watch these machines in action log on to www.raycomfg.com



Model	RG 70	RG 100	RG 100R w/Optional Remote
	Diesel Powered	Diesel Powered	Diesel Powered
Weight - lb (kg)	3,700 (1,678)	3,750 (1,701)	3,750 (1,701)
Length - In (cm)	144 (365.8)	144 (365.8)	144 (365.8)
Height - In (cm)	64 (162.6)	64 (162.6)	64 (162.6)
Width - In (cm)	35 (89)	35 (89)	35 (89)
w/ Dual Wheels - In (cm)	53 (134.6)	53 (134.6)	53 (134.6)
Ground Drive	Self-Propelled Hydraulic, 2-Speed	Self-Propelled Hydraulic, 2-Speed	Self-Propelled Hydraulic, 2-Speed
Engine - hp (kW)	Kubota V3600, 4 Cylinder Diesel, 67 (50)	Kubota V3800DI, 4 Cylinder Diesel, 99.2 (74)	Kubota V3800DI, 4 Cylinder Diesel, 99.2 (74)
Fuel Tank - gal (L)	14 (53)	14 (53)	14 (53)
Super Tooth®	36 Total	36 Total	36 Total
Cutting Depth - In (cm)	21.5 (54.6)	21.5 (54.6)	21.5 (54.6)
Cutting Height - In (cm)	31 (78.7)	31 (78.7)	31 (78.7)
Cutting Width -In (cm)	69 (175.3)	69 (175.3)	69 (175.3)
Cutter Wheel - In (cm)	23 x .75 (58.4 x 1.9)	23 x .75 (58.4 x 1.9)	23 x .75 (58.4 x 1.9)
Controls	4-Lever	4-Lever	Joystick
Optional Wireless Remote	N/A	N/A	Available



Not your average stump cutter. Accept nothing less.



Swing-Wide Chip Retainers



Hydraulic Backfill Blade



Command-Cut Swing Control



RG100R - Optional Wireless Radio Remote Control



4-Wheel Drive w/2-Speed Travel



Power To Take On Big Stumps



Custom Trailer Available



RG100R - Optional Handheld Remote Control

Full Featured. High Power. Top-Notch Performance!

RAYCO's Flagship RG70 and RG100 models are the answer if you're looking for a full-feature, high power backyard stump cutter. These machines feature powerful 66.8 hp and 99.2 hp Kubota diesel engines with hydrostatic cutter wheel drive and RAYCO's Command Cut to deliver top-notch performance. The swing-out control panel provides a good look at the cutting action while keeping the operator safe from flying debris. The RG100R gives you the added feature of radio remote controls, giving the operator the option of using either the swing-out panel or the handheld control unit. A low center of gravity and 4-wheel drive with high and low travel speed get you to the job without turf damage. Standard dual wheels come on and off in minutes to get through 36-inch gates. The hydraulic backfill blade can be used to make short work of clean-up.

Think Smart, Think Safe.....

We care about your safety. When operating your RAYCO machinery always wear an approved helmet complete with ear muffs, face shield and the proper eyewear. Never operate under the influence of alcohol or drugs. Know your RAYCO, read and understand your owner's manual cover to cover.

800.392.2686

CALL TOLL FREE 800.392.2686
(USA or Canada Only)



RAYCO Manufacturing, Inc.
4255 E Lincoln Way
Wooster, Ohio 44691-8601 USA
Phone: 330.264.8699
Fax: 330.264.3697
raycomfg.com

SP-801/901/901R-06/10 (replaces SP-801/901-05/10)
Made and Printed in the USA

Copyright © 2010 RAYCO Manufacturing, Inc., Wooster, OH 44691

RAYCO Manufacturing Inc. retains the right to make changes in design and specifications; engineering; add or remove features; add improvements; or discontinue manufacturing at any time without notice or obligation.